

 **DITCH WITCH®**

SK750 & SK755 COMPACT TOOL CARRIER



The new Ditch Witch® SK750 and SK755 are built to outperform on any jobsite. Both models feature a high-drive track system along with an enhanced operator station, delivering superior performance through increased ground clearance, more lift capacity, faster ground speed, longer track life and more operator comfort. And by sending more horsepower to the attachment than the competition, these new SK mini skid steers will help make you more productive, job after job. Not White. Not Red. Only **Orange**.

KEY FEATURES

- Efficient, low-maintenance Kubota® diesel engines provide outstanding power for all machine functions—24.8 hp (18.5 kW) for the SK750 and 32.8 hp (24.5-kW) for the SK755.
- Industry-leading power to the attachment provides unbeatable productivity; accepts more than 70 attachments for a wide range of utility, landscaping, plumbing, and other underground construction tasks.
- Convenient, pilot-operated controls increase efficiency on the jobsite.
- Belt-free design eliminates worries about slipping, squeaking and breaking.
- Auxiliary hydraulics with quick-connect attachment fittings, so you can perform multiple jobs on the same jobsite in less time.
- 4.7-mph (7.6-km/h) maximum ground drive speed enhances jobsite productivity and efficiency.
- 800-lb (362.9-kg) rated operating capacity and an 81 inch hinge-pin height enables more productive loading.
- Innovative high-drive track system features bolt-on sprockets and wide track rollers for greater stability, longer track life and easy maintenance.
- Low-maintenance track tensioning system features a grease cylinder for easy adjustment and track removal, delivering longer life and minimizing downtime.
- Open track frame is designed for easier, faster cleanup.
- Float section on the lift arm control valve enhances the productivity of attachments that follow the contour of the ground.
- Large platform offers more room and greater comfort for the operator.
- Two-way auxiliary control foot pedal enables you to maintain hydraulic flow to the attachment with the pedal, freeing up your hands to control depth and ground speed.
- Ergonomic operator's station comes standard with dual lever ground drive controls or the option of a single lever joystick.
- Lift-up rear access panel simplifies maintenance and conveniently houses the cold start controls and operator's manual.

 **Ditch Witch®**
ditchwitch.com

SPECIFICATIONS

SK750 & SK755	U.S.	METRIC
DIMENSIONS (STD)		
Operating height, max., std. bucket	103 in	2615 mm
Overall length of machine, std. bucket	105 in	2670 mm
Overall length of loader, no attachment	86 in	2190 mm
Wheelbase/track length	43 in	1092 mm
Min. ground clearance (center/side)	8.9 / 3.7 in	226 / 94 mm
Angle of departure	27°	
Track width, max.	42 in	1065 mm
Track width, min.	36 in	915 mm
Platform height	12.5 in	317.5 mm
Hinge pin height, max.	81 in	2057 mm
PERFORMANCE		
Ground drive speed, forward and reverse	4.7 mph	7.6 km/h
Ground pressure ¹ (ISO/CD 16754)		
7 in (180 mm) tracks	4.8 psi	0.33 bar
9 in (230 mm) tracks	3.8 psi	0.26 bar
Tipping capacity	2,285 lb	1039 kg
Rated operating capacity (35% of tipping capacity)	800 lb	364 kg
Machine weight (no attachment, fluids full)	2,890 lb	1314 kg
HYDRAULIC SYSTEM		
Auxiliary circuit		
Double gear pump		
SK750 Flow rate (Pump #1)	6.5 gpm	24 lpm
SK750 Flow rate (Pump #2)	5.5 gpm	21 lpm
SK755 Flow rate (Pump #1)	8.5 gpm	30 lpm
SK755 Flow rate (Pump #2)	5.5 gpm	21 lpm
Pressure	3,000 psi	207 bar
Ground drive		
Dual hydrostatic pumps		
Pressure	3,500 psi	241 bar
Flow rate	13.9 gpm	52 lpm
POWER		
SK750 - Kubota D1105 diesel engine		
Mfg. gross power rating (SAE J1995)	24.8 hp	18.5 kW
Emissions compliance	EPA Tier 4	
SK755 - Kubota D1105-T diesel engine		
Mfg. gross power rating (SAE J1995)	32.8 hp	24.5 kW
Emissions compliance	EPA Tier 4i	EU Stage IIIA
Number of cylinders	3	
Displacement	68.5 in ³	1.12 L
Bore	3.07 in	78 mm
Stroke	3.09 in	78.4 mm
Rated engine speed	3,000 rpm	
FLUID CAPACITIES		
Hydraulic reservoir capacity	9.2 gal	35 L
Engine oil, with filter	4.2 qt	4 L
Fuel tank capacity	10.5 gal	40 L
BATTERY		
SAE Res. Cap 110 min., SAE cold crank @ 0°F (-1.8°C) 800 amp 12V Electrical System		

¹ Includes machine weight, 175 lb (80 kg) bucket, and 165 lb (75 kg) operator.

